

**12<sup>th</sup> INTERNATIONAL CONFERENCE  
ON STRUCTURAL ANALYSIS  
OF HISTORICAL CONSTRUCTIONS**

**SAHC 2021**

**Online event, 29 Sep - 1 Oct, 2021**

**P. Roca, L. Pelà and C. Molins (Eds.)**



**12<sup>th</sup> INTERNATIONAL CONFERENCE  
ON STRUCTURAL ANALYSIS  
OF HISTORICAL CONSTRUCTIONS**

**SAHC 2021**

**Online event, 29 Sep - 1 Oct, 2021**

A publication of:

**International Centre for Numerical  
Methods in Engineering (CIMNE)**  
Barcelona, Spain



ISBN: 978-84-123222-0-0

Printed by: Artes Gráficas Torres S.L., Huelva 9, 08940 Cornellà de Llobregat,  
Spain

## TABLE OF CONTENTS

Preface .....	7
Supporting Organizations.....	9
Organizers and Committees .....	11
Sponsors .....	15
Summary .....	17
Contents .....	19
Presented Sessions.....	45
Authors Index.....	3661

## PREFACE

The International Conference on Structural Analysis of Historical Constructions (SAHC) was first celebrated in Barcelona in 1995, followed by a second edition also in Barcelona in 1998. Since then, nine subsequent editions have been organized in different countries of Europe, America and Asia. The SAHC conference series is intended to offer a forum allowing engineers, architects and all experts to share and disseminate state-of-art knowledge and novel contributions on principles, methods and technologies for the study and conservation of heritage structures. Through all its successful past editions, the SAHC conference has become one of the topmost periodical opportunities for scientific exchange, dissemination and networking in the field.

During the last decades the study and conservation of historical structures has attained high technological and scientific standards. Today's practice involves the combination of innovative non-destructive inspection technologies, sophisticated monitoring systems and advanced numerical models for structural analysis. More than ever, it is understood that the studies must be performed by interdisciplinary teams integrating wide expertise (engineering, architecture, history, archeology, geophysics, chemistry...). Moreover, the holistic nature of the studies, and the need to encompass and combine the different scales of the problem –the materials, the structures, the building aggregates, and the territory – are now increasingly acknowledged. Due to all this, the study of historical structures is still facing very strong challenges that can only be addressed through sound international scientific cooperation.

Taking these ideas in mind, the 12<sup>th</sup> edition of the SAHC conference aimed at creating a new opportunity for the exchange and discussion of novel concepts, technologies and practical experiences on the study, conservation and management of historical constructions.

The present proceedings include the papers presented to the conference, which was finally celebrated on September 29-30 and October 1, 2021, in an on-line mode due to the world sanitary emergency situation created by the Covid-19 pandemic.

The conference included the following topics: history of construction and building technology; inspection methods, non-destructive techniques and laboratory testing; numerical modeling and structural analysis; structural health monitoring; repair and strengthening strategies and techniques; conservation of 20<sup>th</sup> c. architectural heritage; seismic analysis and retrofit; vulnerability and risk analysis and interdisciplinary projects and case studies.

The SAHC 2021 conference has been possible thanks to the large contribution of the scientific committee and reviewer panel who took care of selecting and review the papers submitted. The contribution of the different sponsors and supporting organizations is also acknowledged. Above all, the conference has been possible thanks to all the authors who have contributed with very valuable papers despite the difficulties caused by the world pandemic. New editions of the conference are already planned in normal face-to-face formats which, in the upcoming years, will provide new opportunities for sharing valuable knowledge and experience on structural conservation, as well as for keeping alive and fulfilling the purpose and aims of the SAHC conference series.

The Organizing Committee

## SUPPORTING ORGANIZATIONS



**UNIVERSITAT POLITÈCNICA  
DE CATALUNYA  
BARCELONATECH**

Universitat Politècnica de Catalunya  
(UPC), Barcelona, Spain

**CIMNE** 



Center for Numerical Methods in  
Engineering (CIMNE), UPC, Spain



**ICOMOS**  
international council on monuments and sites

International Council on Monuments  
and Sites (ICOMOS)

  
**Iscarsah**  
International Scientific Committee on the Analysis and  
Restoration of Structures of Architectural Heritage

International Scientific Committee for  
Analysis and Restoration of Structures  
of Architectural Heritage of ICOMOS  
(ICOMOS / ISCARSAH)

# ORGANIZERS AND COMMITTEES

## Organizing Committee



**Pere Roca**

Technical University of Catalonia



**Climent Molins**

Technical University of Catalonia



**Luca Pelà**

Technical University of Catalonia



**Paulo Lourenço**

University of Minho



**Claudio Modena**

University of Padova

# SCIENTIFIC COMMITTEE

## National Members

- Jose M. Adam, Polytechnic University of Valencia
- Ernest Bernat, Polytechnic University of Catalonia
- Pedro Calderón, Polytechnic University of Valencia
- Miguel Cervera, Polytechnic University of Catalonia
- Victor Compán, University of Seville
- Leire Garmendia, University of the Basque Country
- Lluís Gil, Polytechnic University of Catalonia
- Pilar Giráldez, University of Barcelona
- Salvador Ivorra, University of Alicante
- Miquel Llorens, University of Girona
- Ignacio Lombillo, University of Cantabria
- Camilla Mileto, Polytechnic University of Valencia
- Javier Mosteiro, Technical University of Madrid
- Belén Riveiro, University of Vigo
- Savvas Saloustros, Polytechnic University of Catalonia
- Fernando Vegas, Polytechnic University of Valencia
- Marius Vendrell, University of Barcelona

## International Members

- Rafael Aguilar, Pontifical Catholic University of Peru
- Takayoshi Aoki, Nagoya City University
- Alessandra Aprile, University of Ferrara
- Oriol Arnau, National Autonomous University of Mexico
- Görün Arun, Yildiz Technical University
- Hiram Badillo, Autonomous University of Zacatecas
- Andrea Benedetti, University of Bologna
- Rita Bento, University of Lisbon
- Katrin Beyer, Swiss Federal Institute of Technology in Lausanne
- Rubén Boroscchek, University of Chile
- Guido Camata, University of Chieti-Pescara
- Claudia Cancino, Getty Conservation Institute
- Eva Coïsson, University of Parma
- Dina D'Ayala, University College London
- Gianmarco de Felice, Roma Tre University
- Gianfranco de Matteis, University of Campania
- Matthew DeJong, University of California at Berkeley
- Milos Drdácáký, Institute of Theoretical and Applied Mechanics
- Khalid El Harrouni, National School of Architecture
- Ahmed Elyamani, Cairo University
- Yohei Endo, Shinshu University
- Mariana Esponda, Carleton University
- Antonio Formisano, University of Naples Federico II
- Dora Foti, University of Bari
- Enrico Garbin, University of Padova
- Giorgia Giardina, University of Cambridge



- Toshikazu Hanazato, Mie University
- Mehrdad Hejazi, University of Isfahan
- Marcela Hurtado, Federico Santa María Technical University
- Jason Ingham, University of Auckland
- Wolfram Jager, Technical University Dresden
- Stephen J. Kelley, SJK Inc.
- Debra Laefer, New York University
- Sergio Lagomarsino, University of Genova
- Alessandra Marini, University of Bergamo
- Guillermo Martínez, Michoacan University of Saint Nicholas of Hidalgo
- Arun Menon, Indian Institute of Technology Madras
- Gabriele Milani, Polytechnic University of Milan
- John Ochsendorf, Massachusetts Institute of Technology
- Daniel Oliveira, University of Minho
- Fernando Peña, National Autonomous University of Mexico
- Andrea Penna, University of Pavia
- Maurizio Piazza, University of Trento
- Mariapaola Riggio, Oregon State University
- Jan Rots, Delft University of Technology
- Antonella Saisi, Polytechnic University of Milan
- Cristián Sandoval, Pontifical Catholic University of Chile
- Vasilis Sarhosis, The University of Leeds
- Yaacov Schaffer, Israel Antiquities Authority
- Nigel Shrive, University of Calgary
- Marek Sklodowski, Institute of Fundamental Technological Research
- Pierre Smars, National Yunlin University of Science and Technology
- Luigi Sorrentino, Sapienza University of Rome
- Enrico Spacone, University of Chieti-Pescara
- Nicola Tarque, Pontifical Catholic University of Peru
- Adrienn Tomor, University of the West of England
- Daniel Torrealva, Pontifical Catholic University of Peru
- Maria Rosa Valluzzi, University of Padova
- Koenraad Van Balen, KU Leuven
- Humberto Varum, University of Porto
- Els Verstryngge, KU Leuven
- Elizabeth Vintzileou, National Technical University of Athens
- Roko Žarnić, University of Ljubljana

## REVIEWER PANEL

- Daniela Addessi
- Maurizio Angelillo
- Jesus Bairán
- Elisa Bertolesi
- Maria Bostenaru
- Giuseppe Brando
- Manuel Buitrago Moreno
- Albert Cabané
- Chiara Calderini
- Ivo Calì
- Lorenzo Cantini
- Silvia Caprili
- Giuliana Cardani
- Claudia Casapulla
- Rosario Ceravolo
- Francesca Ceroni
- Francesco Clementi
- Camilla Colla
- Cossima Cornadó
- Sara Dimovska
- Anastasios Drougkas
- Chiara Ferrero
- Virginia Flores Sasso
- Aguinaldo Fraddosio
- Donald Friedman
- Stefano Galassi
- Larisa García-Ramonda
- Lucia Garijo
- Carmelo Gentile
- Lorenzo Jurina
- Philip Karklbrenner
- David López
- Jose Machado
- Nirvan Makoond
- Nuno Mendes
- Andronki Miltiadou
- Bernt Mittnacht
- Tom Morrison
- Marius Mosoarca
- Juan Murcia
- Federica Ottoni
- Bartolomeo Pantò
- Marisa Pecce
- Chiara Pepi
- Elisa Poletti
- Bora Pulatsu
- Enrico Quagliarini
- Luisa Rovero
- Nicola Ruggieri
- Santiago Sanchez
- Mario Santana
- Michel Schuller
- Jorge Segura
- Vincenzo Sepe
- Alberto Taliercio
- Dimitris Theodossopoulos
- Filippo Ubertini
- Giuseppina Uva
- Graça Vasconcelos
- Maria Belén Jiménez

## SPONSORS

PRO\_SAM is a plugin which connects PRO\_SAP with SAM II solver, a powerful tool for pushover analysis of new and existing structures.

### SOLVER RELIABILITY

SAM II, conceived by Prof. Magenes, Eng. Manzini and Eng. Morandi, is a well-known and robust non-linear solver highly referenced in international literature.

### CODES OF PRACTICE

Eurocode 8, Italian codes.

### MATERIALS

Unreinforced and reinforced masonry, reinforced concrete and generic linear materials.

### LOCAL FAILURE MECHANISMS

Automatic geometry interfacing with PRO\_CineM for kinematic linear and non-linear analyses.

### LINEAR ANALYSIS

Automatic generation of plate and shell linear model from the equivalent frame.

### FREE

PRO\_SAM is free for students, scholars or scientific research.



Asdea Software S.r.l. is part of the burgeoning ASDEA brand, which includes ASDEA S.r.l. and ASDEA Hardware. We are a software development company staffed with engineers, researchers, and software developers. Our goal is to provide innovative software solutions customized for clients and of original in-house design for numerical simulation and data visualization. We are the company behind the revolutionary software STKO (Scientific ToolKit for OpenSees). More than just a simple GUI, STKO features a Python scripting interface, meaning that users can customize and program the already powerful pre and postprocessors as needed, harnessing the full power of OpenSees.



CALSENS develops state-of-the-art fiber-optic sensors and designs, deploys and operates structural health monitoring (SHM) solutions to monitor bridges, buildings and vehicles (ships, airplanes, UAV), among other structures. Our services are based on constant research and innovation, creating products and services at the frontier of knowledge.

CALSENS services cover the full process of monitoring. Starting from the modelling of structural behavior and choice of control parameters, continuing with the election, design, fabrication and installation of the sensors and sensing system, until the processing, interpretation and evaluation of the data.

CALSENS has a multidisciplinary team with a high degree of expertise in the fields of civil engineering, photonic technologies, signal processing, materials engineering or computing.





Kerakoll is the international leader in the GreenBuilding sector, providing solutions that safeguard the health of both the environment and the people.

The company mission is embrace and promote GreenBuilding as the new low environmental impact approach to building and promote higher quality homes around the world through the use of eco-friendly building materials and innovative solutions.

Since 1968 – when the Group was founded in Sassuolo– Kerakoll has been pursuing a clear course of development in Italian and international markets for building materials, that has taken the company to the forefront of the GreenBuilding industry and to a level of technological supremacy famous around the globe.



S.T.A. DATA, founded in 1982 by Adriano Castagnone, civil and structural engineer since 1978, and pioneer of scientific software for structural engineering, is composed of more than 20 people, all highly qualified professionals. Our aim is to offer software for structural calculation that allow designers to face everyday work with simplicity and effectiveness.

S.T.A. DATA offers 3Muri Project, developed specifically for masonry.

In fact, it is not a generic Finite Element software adapted for masonry structures; 3Muri Project was born from the specific research for these structures and captures all the characteristics to obtain a safe and reliable calculation of historical, existing and new buildings.



IRS is a smart Engineering, Research and Development company founded by a group of engineers in 1993. IRS Structural Health Monitoring division designs, develops and integrates automated systems for mechanical and structural monitoring. Thanks to technological innovation, advanced modeling and design as well as professional production and after sales service provide a complete suite of structural health monitoring solutions. Monitoring version are both portable version for laboratory tests and one shot structural assessments and long term and in situ applications like historical sites, buildings, bridges, dams and tunnels. IRS is part of a group of companies including Measureit, with whom provides consultancy and sales of precision sensor and data acquisition systems.

# SUMMARY

## PRESENTED SESSIONS

Conservation of 20th c. architectural heritage .....	47
History of construction and building technology.....	200
Inspection methods, non-destructive techniques and laboratory testing.....	481
Interdisciplinary projects and case studies .....	873
Management of heritage structures and conservation strategies .....	1514
Numerical modeling and structural analysis.....	1675
Repair and strengthening strategies and techniques.....	2439
Resilience of historic areas to climate change and hazard events .....	2746
Seismic analysis and retrofit .....	2846
Structural health monitoring.....	3206
Vulnerability and risk analysis .....	3390

## **Vulnerability and risk analysis**

- A Comparison Between Empirical Procedures for the Definition of Vulnerability Classes of Masonry Buildings: Application to Five Historical Centres Struck by 2016 Central Italy Earthquake** ..... 3390  
*Y. Saretta, L. Sbrogiò and M.R. Valluzzi*
- A QGIS Plugin for the Seismic Vulnerability Assessment of Urban Centers: Application to the City of Popoli in Abruzzo (Italy)** ..... 3402  
*A. Gonzalez, A. Basaglia, E. Spacone and G. Brando*

<b>Assessment of Seismic Fragility of Historical Buildings at the Urban Scale by Typological-Mechanical Approaches: the Case Study of Foggia</b> .....	3414
<i>V. Leggieri, S. Ruggieri and G. Uva</i>	
<b>Criteria for the Vulnerability Analysis of Structural Aggregates in Historical Centers</b> .....	3426
<i>S. Tonna, M. Boriani, M.C. Giambruno and C. Chesi</i>	
<b>Development of a Fire Damage Index for Immovable Cultural Heritage</b> .....	3438
<i>L.G. Salazar, E. Paupério and X. Romão</i>	
<b>Evaluation of Invasive Retrofitting Interventions on an Unreinforced Masonry Heritage Building</b> .....	3450
<i>A. Scupin, R. Vacareanu and F. Pavel</i>	
<b>Kinematic Approach for Seismic Vulnerability Assessment of Masonry Churches</b> .....	3462
<i>V. Corlito, G. De Matteis and P. Roca</i>	
<b>Managing Natural Disasters in Historic Areas: a Novel Holistic Seismic Risk Assessment Method Applied to a Relevant Case Study</b> .....	3474
<i>E. Quagliarini, G. Bernardini and M. Lucesoli</i>	
<b>Risk Assessment Methodologies to Safeguard Historic Urban Areas from the Effects of Climate Change</b> .....	3486
<i>L. Quesada-Ganuza, L. Garmendia, E. Rojí, I. Álvarez, E. Briz and M. Olazabal</i>	
<b>Risk Management and Built Heritage: Towards a Systematic Approach</b> .....	3498
<i>A. Konsta and S. Della Torre</i>	
<b>Seismic Damage Scenarios Induced by Site Effects of Masonry Clustered Buildings: a South Italy Case Study</b> .....	3510
<i>A. Formisano and N. Chieffo</i>	
<b>Seismic Vulnerability Assessment Method for Vernacular Architecture Considering Uncertainty</b> .....	3522
<i>J. Ortega, S. Saloustros and P. Roca</i>	
<b>Seismic Vulnerability Assessment Methodology for Historical Buildings with Cultural Value</b> .....	3534
<i>E. Onescu, I. Onescu and M. Mosoarca</i>	
<b>Seismic Vulnerability Assessment of a Historic Brick Masonry Building by Fragility Functions</b> .....	3546
<i>K. Demirlioglu and S. Soyoz</i>	
<b>Seismic Vulnerability Assessment of Representative Building Typologies from Barcelona's Eixample District</b> .....	3557
<i>S. Dimovska, S. Saloustros, L. Pelà and P. Roca</i>	

<b>Seismic Vulnerability Assessment of Romanian Historical Building under Near-Source Earthquake .....</b>	<b>3569</b>
<i>N. Chieffo, M. Mosoarca, A. Formisano and P.B. Lourenço</i>	
<b>Seismic Vulnerability of Heritage Churches in Québec: the Néo-Roman Typology .....</b>	<b>3581</b>
<i>G. Sferrazza Papa, M-J. Nollet and M.A. Parisi</i>	
<b>Simplified Seismic Vulnerability Assessment of Medieval Masonry Churches .....</b>	<b>3593</b>
<i>V. Corlito, M. Zizi and G. De Matteis</i>	
<b>The Assessment and Reduction of Seismic Risk: Towards a System of Knowledge for Archaeological Pre-Existences .....</b>	<b>3605</b>
<i>E. Montenegro</i>	
<b>The Damage Survey of Cultural Built heritage Between Simplified Procedures and Needs for Implementation: the Case Study of Emilia-Romagna Cemeteries .....</b>	<b>3617</b>
<i>V. Vona and M. Zuppiroli</i>	
<b>Typological Classification and Observed Damage Patterns of Masonry Churches After the 2016 Central Italy Earthquake .....</b>	<b>3629</b>
<i>G. Cianchino, C. De Matteis and G. Brando</i>	
<b>Vulnerability Assessment of Dwellings in the Historic Center of Cusco (Peru) .....</b>	<b>3640</b>
<i>G. Brando, G. Cocco, C. Mazzanti, M. Peruch, E. Spacone, C. Alfaro, K. Sovero and N. Tarque</i>	
<b>Vulnerability Assessment of Italian Unreinforced Masonry Churches Using Multi-Linear Regression Models .....</b>	<b>3649</b>
<i>A. Marotta, D. Liberatore and L. Sorrentino</i>	



## CRITERIA FOR THE VULNERABILITY ANALYSIS OF STRUCTURAL AGGREGATES IN HISTORICAL CENTERS

S. TONNA<sup>1</sup>, M. BORIANI<sup>2</sup>, M. C. GIAMBRUNO<sup>3</sup>, C. CHESI<sup>4</sup>

<sup>1</sup> Politecnico di Milano – DASTU Department  
Piazza Leonardo da Vinci, 32 – 20133 Milano, Italy  
e-mail: [sandra.tonna@polimi.it](mailto:sandra.tonna@polimi.it) (\*corresponding author)

<sup>2</sup> Politecnico di Milano – DASTU Department  
Piazza Leonardo da Vinci, 32 – 20133 Milano, Italy  
e-mail: [maurizio.boriani@polimi.it](mailto:maurizio.boriani@polimi.it)

<sup>3</sup> Politecnico di Milano – DASTU Department  
Piazza Leonardo da Vinci, 32 – 20133 Milano, Italy  
e-mail: [mariacristina.giambruno@polimi.it](mailto:mariacristina.giambruno@polimi.it)

<sup>4</sup> Politecnico di Milano – A.B.C. Department  
Piazza Leonardo da Vinci, 32 – 20133 Milano, Italy  
e-mail: [claudio.chesi@polimi.it](mailto:claudio.chesi@polimi.it)

**Keywords:** Aggregate, historical center, seismic vulnerability, on-site survey

**Abstract.** *The need to define earthquake prevention and intervention strategies, in order to limit dramatic consequences for the society, has acquired a high priority in countries where, like in Italy, a large number of historic masonry buildings (listed or not) are located in areas with medium to high seismic hazard. From the point of view of the level of safety to be reached through interventions, the concept of improvement, as opposed to that of full strengthening, is nowadays widely accepted in the case of monumental heritage; what is still lacking, in many cases, is a procedure for the vulnerability analysis, as a synthetic evaluation tool for the definition of intervention priorities. In a modern perspective, where territorial planning is conceived as a safety project for the territory, the seismic vulnerability analysis should not be confined to specific technical documents, but should rather be considered at a general level; in this way only, indeed, the issue of seismic risk could acquire widespread knowledge and awareness in the population, also pushing urban planning in the direction of general programs for the increase of seismic safety. In the above perspective, revised criteria have to be developed for a global vulnerability assessment, to be introduced at a general level in territorial planning. Considering that seismic vulnerability analyses are strictly dependent on specific building typologies, attention has been focused, in the present study, on to the case of structural aggregates in historical centers, thus following the needs of the Italian Civil Protection Agency in relation to seismic prevention activities in historical towns. The research, which is still in progress, takes advantage from the application to a few study cases, suitable for the experimental testing of procedures.*

## 1 INTRODUCTION

The frequent recurrence of seismic events in Italy in recent times has stressed the need, for the society, to develop effective levels of preparedness, in order to reduce the negative impact on the safety of people, the conservation of the built environment, and the continuity of normal life. To this purpose, the seismic vulnerability analysis of buildings and public works in general is a fundamental prevention tool; within this context, vulnerability has to be intended in its original meaning, i.e., a fast qualitative evaluation of the inclination, for the structure, to suffer damage from an earthquake. Based on meaningful indicators, not necessarily of a structural nature, the vulnerability analysis is therefore suitable for being applied to large groups of buildings with a statistical purpose.

Originally, vulnerability analyses were conceived in view of risk reduction strategies with the purpose of highlighting the possible lack of seismic resistance, thus suggesting consolidation interventions and favouring seismic damage prevention. In recent times, as a consequence of the development of effective and well organized Civil Protection Services for natural disasters and, in particular, earthquakes, vulnerability analyses have also been recognized as the necessary tool for a positive management of emergency situations, in the sense of supporting preparedness to damage scenarios.

Starting from the traditional approach to vulnerability evaluations, based on the analysis of single structural units, new procedures have now to be formulated, extending consideration to entire structural aggregates, in view of the development of wide damage scenarios at the urban scale. Recently, this specific need has been formulated by the Italian Civil Protection Agency as a support to the development of Civil Protection plans; specifically, in accordance with the typical nature of the Italian built environment, the study is focused on the vulnerability analysis of historical aggregates of ancient urban centers (Fig. 1).



**Figure1:** Typical views of historical aggregates.

The paper presents the criteria adopted for the re-formulation of traditional vulnerability analyses at the scale of aggregates of structural units, in the spirit of a qualitative analysis for

a fast application at a wide scale, taking advantage of the numerous studies on seismic vulnerability procedures which have been developed through time.

## 2 THEMATIC FRAMEWORK

The vulnerability analysis, as originally conceived [1], clearly showed the possibility of developing the formal implementation of a qualitative approach to the analysis of the seismic capacity of masonry buildings. This was supported by the high degree of knowledge which had been reached in relation to the seismic performance of masonry buildings, as a result of the repeated post earthquake field surveys documenting typical damage modalities, followed by analytical interpretations. Specifically, vulnerability analyses focused on the occurrence of the structural details which have been generally recognized in favour of the positive performance of a masonry building under the effect of seismic actions; typically, wall-to-wall connections, diaphragmatic behaviour of floor slabs, shear resistance of masonry piers, etc [1, 2, 3].

At present, in consideration of the remarkable growth of experience in this field in recent times, qualitative approaches to the evaluation of masonry structures are even more justified [4, 5, 6, 7]. In addition to vulnerability analyses, indeed, similar procedures have been developed in relation to other needs. Meaningful examples are given by the special form which is normally used in Italy for the evaluation of buildings after a seismic event in terms of the possibility of safe access and usage, and by the procedure for the definition of seismic risk classes for residential buildings.

It is also of interest to recall that the application of the above qualitative procedures for the assessment of seismic safety, not requiring analytical computations, is not for civil engineers only, but can be extended to all those who have a professional activity related to buildings and, through an experience based knowledge, have developed sensitivity on construction details and structural behaviour.

Vulnerability analyses were originally based on the field inspection of single structural units; a fast survey was normally performed by a specially trained team, and completed within a few hours, filling in a form and evaluating, as a final result, the vulnerability index.

Extending such procedure to the case of aggregates, still preserving the nature of a fast qualitative evaluation, new meaningful parameters have to be identified for a correct interpretation of the structural behaviour. Also, it has to be considered that the vulnerability analysis, in this case, is mainly addressed to the needs of Civil Protection plans and, therefore, the identification of situations involving high danger levels.

Looking at typical aspects characterizing the seismic response, attention has to be focused primarily onto structural regularity, degree of connection of the different units, and possible transformations occurred through time, which may have altered the original structural layout. All this has to be recognized through a simple visual inspection of the different fronts of the aggregate.

More in detail, the issue of plan and elevation irregularities now corresponds to a generally acquired concept, normally addressed also by building codes. It has to be considered that both irregularity forms may be enhanced in the case of an aggregate, thus assuming a special relevance in terms of potential damage. Similarly, the degree of connection of different parts, which has normally to do with the connection of wall panels and floor slabs within a single

building, has to be extended to the scale of the aggregate in terms of interaction of the different structural units.

Finally, having to do with historical aggregates, modifications of the original resisting system may have been introduced due to changes in the usage conditions of the building; in some cases such modifications may have seriously compromised the lateral strength of the building.

The above considerations clearly show that a qualitative approach to the evaluation of the seismic vulnerability of an aggregate is meaningful and, probably, should be always considered before developing accurate models for the analysis of single structural units. The original concept of a vulnerability analysis, therefore, is totally justified also in the case of aggregates in relation to the present needs of analysing seismic safety.

### 3 URBAN-LEVEL VULNERABILITY ANALYSIS

Several research works [3, 8, 9, 10] have been addressed to the analysis of seismic vulnerability in historical centers, showing a wide variety in the methodological trends. All the analyzed methods can be classified on the basis of a single criterion according to the assumptions done for the investigation scale and the analytical approach. Following the classification proposed by [10, 11], the various methodologies can be organized, from the point of view of the analysis scale, into three macro-groups (*urban, district, building*) and each of these can be further organized into sub-categories, in relation to the method of analysis (*direct, indirect, conventional and hybrid*) [12, 13, 14, 15, 16].

For the research in progress, the most appropriate reference key is the urban one, as it provides a methodology for a global view of a stratified *urban* fabric constituted of more or less connected structural aggregates. Among the different proposals, attention has been addressed to the methodologies defined as "indirect" and "hybrid". These make reference to a homogeneous group of buildings, which is globally assigned the vulnerability index of a model case, which was analyzed through an in-depth study. Such methods are both derived from the criterion proposed by Benedetti & Petrini in 1984 [1], which was the base for the formulation of the first and second level vulnerability analyses. It is still in use at the international level and has inspired all the other methodologies for vulnerability analysis which were introduced subsequently.

In the various alternatives, modifications to the original method concerned both the scale (from building to aggregate), and the methodology for the choice of the pilot case. Recently, indeed, an opposite approach has been introduced: following a general investigation of the whole urban center, the most representative case studies are selected for a second phase in-depth research [5, 6, 12].

Finally, to the purpose of a really effective vulnerability analysis, a critical issue is given by the choice of the evaluation parameters and the definition of the relative weighting coefficients. In the original formulation by Benedetti & Petrini [1] eleven parameters were defined; among these, only one was based on a numerical evaluation (item 3 in Table 1), two accounted for general aspects (items 10 and 11 in Table 1), while the remaining eight parameters were based on a qualitative evaluation of structural aspects. In recent works [8, 11] the number of the parameters has increased to 14 [8] or 15 [11], in order to take into

account stratifications occurred with time and interactions among structural units within the aggregate.

Tables 1, 2, and 3 show details about the different procedures developed by Benedetti & Petrini in 1984 [1], Vincente in 2011 [8], and Ferreira in 2017 [11], respectively.

Methodologies present differences in the selection and ordering of the vulnerability parameters and in the relative weighting coefficients, whereas all of them make reference to four vulnerability classes (A-B-C-D) for the evaluation of each single parameter.

**Table 1:** Items considered in the Benedetti & Petrini, vulnerability index method [1]

Item n.	Parameters	Class				Weight
		A	B	C	D	
1.	Type and organization of the lateral force resisting system	0	5	20	45	1.00
2.	Quality of the resisting system	0	5	25	45	0.25
3.	Conventional strength	0	5	25	45	1.50
4.	Position of building and foundations	0	5	15	45	0.75
5.	Floor systems	0	5	25	45	variable
6.	Horizontal layout regularity	0	5	25	45	0.50
7.	Regularity in elevation	0	5	25	45	variable
8.	Maximum distance between parallel walls	0	5	25	45	0.25
9.	Roof system	0	15	25	45	variable
10.	Non-structural elements	0	0	25	45	0.25
11.	Present state of the building	0	5	25	45	1.00

In the approach developed by Vincente vulnerability parameters are grouped into four categories. In comparison to the approach by Benedetti & Petrini, one parameter is modified, shifting the attention from the structural unit to the aggregate (P7) and 2 more are introduced: opening alignment on the facade (P10) and aggregate fragilities (P13).

As far as vulnerability classes (A-B-C-D) are concerned, they are associated to similar scores, with the only differences in class C, where the value is decreased to 20, and class D, where it is increased to 50. Weighting coefficients also present differences, being always associated to fixed values.

Ferreira, like Benedetti & Petrini, makes reference to individual parameters, without grouping them into categories. The vulnerability analysis of the aggregate is based on fifteen parameters, considering also structural stratifications and the presence of typological or structural heterogeneities between adjacent buildings (item n. 14). Modifications in the vulnerability classes are also present, due to the introduction of negative values for parameters 11, 12, 14, and 15; fixed values are used for weighting coefficients.

Through a quick comparison of the above procedures, differences can be easily identified: vulnerability analysis, initially addressed to a single structural unit, is then extended to a structural aggregate and, consequently, the choice of parameters is different. Moreover, while the original method was based on a field survey of the building to be performed from both

outside and inside, the other two are more concentrated on the external survey of the building; in addition, they are structured in order to allow for an easier final calculation.

**Table 2:** Items considered in the Vincente, vulnerability index method [8]

Item n.	Categories and Parameters	Class				Weight
		A	B	C	D	
1.	Structural building system					
	<i>P1. Type of the resisting system</i>	0	5	20	50	0.75
	<i>P2. Quality of the resisting system</i>	0	5	20	50	1
	<i>P3. Conventional strength</i>	0	5	20	50	1.50
	<i>P4. Maximum distance between walls</i>	0	5	20	50	0.50
	<i>P5. Number of floors</i>	0	5	20	50	1.50
	<i>P6. Location and soil conditions</i>	0	5	20	50	0.75
2.	Irregularities and interactions					
	<i>P7. Aggregate position and interactions</i>	0	5	20	50	1.50
	<i>P8. Plan configuration</i>	0	5	20	50	0.75
	<i>P.9 Regularity in height</i>	0	5	20	50	0.75
	<i>P10. Wall facade openings and allignments</i>	0	5	20	50	0.50
3.	Floor slabs and roof					
	<i>P11. Horizontal diaphragms</i>	0	5	20	50	1.00
	<i>P12. Roofing systems</i>	0	5	20	50	1.00
4.	Conservation status and other elements					
	<i>P13. Fragilities and conservation state</i>	0	5	20	50	1.00
	<i>P14. Non-structural elements</i>	0	5	20	50	0.50

**Table 3:** Items considered in the Formisano et al.,vulnerability index method [11]

Item n.	Parameters	Class				Weight
		A	B	C	D	
1.	Organization of the vertical resisting system	0	5	20	45	1.00
2.	Type of the vertical resisting system	0	5	25	45	0.25
3.	Position of building and foundations	0	5	25	45	0.75
4.	Resistant elements distribution in plan	0	5	25	45	1.50
5.	Regularity in plan	0	5	25	45	0.50
6.	Regularity in elevation	0	5	20	45	1.00
7.	Floor systems	0	5	25	45	0.75
8.	Roof system	0	15	25	45	0.75
9.	Details	0	0	25	45	0.25
10.	Present state of the building	0	5	20	45	1.00
11.	Altimetric interaction	-20	0	15	45	1.00
12.	Planimetric interaction	-45	-25	-15	0	1.50
13.	Horizontal layout regularity	0	15	25	45	0.50
14.	Typological and structural discontinuities	-15	-10	0	45	1.20
15.	Percentage difference between full and openings in the facade	-20	0	25	45	1.00

In the present research, the proposal of a new method for vulnerability analyses has benefited from all the previous works; in particular, in line with the approach by Vincente [8], the grouping of vulnerability parameters into macro-classes has been adopted, as it allows for a more effective management of on-site surveys, a better organization of data and, globally, a faster procedure. Criteria for the development of the new procedure are illustrated in the following, together with implementation details.

#### 4 A PROPOSAL FOR A METHODOLOGY BASED ON KNOWLEDGE LEVELS

Procedures for the evaluation of seismic vulnerability are based on the definition of a set of meaningful parameters, from which a realistic view of the seismic capacity of the structure can be obtained. This is not a purely theoretical process, as the effectiveness of the selected parameters has to be verified on the field through the analysis of selected case studies. Specifically, an iterative multi-step procedure has to be undertaken, with continuous testing and updating of the evaluation process, until a fast, clear and stable procedure is defined, providing as much as possible user independent results.

Such a process has been started within the current research work and is still in progress; it is believed, however, that the implementation of the final version of a data sheet to be systematically used for on-site applications should come soon to an end. The final product, resulting from the iterative process, will reflect the original idea of a two-step procedure, consisting in a first phase dedicated to the collection of meaningful documents, followed by the field inspection of the buildings, as it is detailed in the following. Also, the original criterion for the field analysis has been confirmed, based on the following sequence:

- select a front of the structural aggregate,
- recognize all structural units,
- evaluate each of them in relation to six categories of parameters,
- define, for each parameter, the vulnerability level as: *low* (A), *medium-low* (B), *medium-high* (C), *high* (D).

Details about the two-step procedure are discussed in the following. As previously mentioned, this vulnerability analysis is intended for use in the specific case of structural aggregates in historical centers; masonry, therefore, is the main reference material.

##### 4.1 Investigation method

As known, it has become a common practice, well reflected also in building codes, to base the analysis of existing buildings on the acquisition of all the available information, coming to the definition of a specific knowledge level. Normally, information is collected with reference to the building historical analysis, the characterization of structural properties (typology, material, geometry), and action definition.

In the present research it was believed of interest to organize the vulnerability analysis from the point of view of two different knowledge levels: a first one (KL0), consisting in the collection of meaningful documentation from historical archives, municipality offices, and web data (typically, Google Maps), and a second one (KL1), consisting in the field inspection of the aggregate under study. This should be limited, in general, to the external survey of the aggregate fronts but might require, in some cases, a more detailed one to be performed at a

second time (KL2), based on the internal inspection of buildings and a deeper analysis of the archival documentation.

Clearly, the original formulation of the vulnerability analysis [1] simply consisted in the field survey, while the recognition of different knowledge levels belongs to recent studies and is still under testing [17]. In any case, the added value coming from the analysis of documents marks a meaningful increase in the relevance of vulnerability analysis, also allowing for a lower accuracy level in the field inspection.

Details about the two phases in the knowledge acquisition process are given in the following.

## 4.2 Analysis of documents

The phase defined as KL0 is aimed at providing the vulnerability analysis with a minimum knowledge of the building under consideration in view of the on-site survey and the consequent qualitative assessment and classification within vulnerability categories. The parameters to be considered in this phase can all be analyzed in the office through the inspection of several documents, as listed in the following; a major outcome of this analysis would be in the possibility of highlighting the transformations occurred over time through the comparison of the intended use, as noticed in the historical registers, with the current one. Structural transformations may have a remarkable effect on seismic vulnerability; a typical case, frequently occurring, is given by the presence of large openings at the ground floor, which were not present in the original building configuration (Fig. 2). Normally, this kind of intervention is done providing a suitable propagation path to the vertical loads, with no consideration of horizontal actions; the soft-story configuration is therefore automatically generated.

During this phase, the historical center and its aggregates will be investigated through the analysis of the following data and parameters:

1. Archival data, with the main purpose of comparing the intended building use and quality, as described in the historical land registers, with the current classifications.
2. Where available, the damage evaluation forms which are normally filled after an earthquake for a first assessment of the building conditions in terms of possible use and restoration needs. In Italy, the "AeDES" form has been developed to this purpose and is normally available in the municipality offices [18].
3. General information at the territorial level, as the urban morphology, its historical development and the topographic profile of the historical center.
4. Ratios between building height and road width and structural connections with neighboring aggregates (Fig. 1).
5. In the presence of a ground slope, the aggregate orientation with respect to the contour lines.
6. The aggregate morphology, namely, regularity in plan, any front offset, or the presence of internal courtyards.
7. The general aggregate conservation status.





**Figure 2:** Transformations: a) XX century image of a traditional Italian historical center with the detail of a three storey building, b) widening of the original openings, compromising resistance to horizontal actions.

### 4.3 On-site survey

The next phase, KL1, is based on the analysis of the actual state of the structural aggregate through the qualitative survey of each external front. The main purpose is identifying both structural and architectural characteristics, the current usage conditions and the maintenance state for each facade of the aggregate. This on-site investigation will lead to the achievement of a vulnerability classification for the entire front on the basis of the evaluation of each single structural unit and of its possible interaction with the adjacent ones.

This phase is organized so that the six categories of parameters, as detailed in the following, can be assessed simultaneously for each structural unit of the front under examination:

1. The vertical resisiting system, through the relationship between full and empty spaces and openings alignments. In addition, the presence of openings wider than 2 m in order to recognize the possible presence of a soft story condition.
2. Fragilities and interactions, through the survey of material inhomogeneity, added portions in elevation, filling of separation joints.

3. Fragilities in structural units, i.e., the presence of porches, covered walkways, slender elements, large and empty structural units within the aggregate (churches and theatres), chimneys and elements protruding on the road (Figs. 3, 4).
4. The conservation status through all its variants, such as surface degradation, presence of superficial or deep cracks, local collapses.
5. Protruding roof structure, as detectable from the street. The materials and the state of conservation will be indicated.
6. Seismic protection elements belonging to local building techniques, such as buttresses, contrast arches, chains and tie rods, blind arches in the masonry, cantonal, structural joints.

As previously commented, the recourse to a KL2 phase might also be required, in case a deeper knowledge of the building structural conditions is required. This, however, is believed to be a special case,

#### **4.4 A vulnerability index**

As a result of the two-level evaluation procedure, a number of parameters are assigned to one of the vulnerability classes, A, B, C, or D. In traditional vulnerability analyses, as previously recalled, each vulnerability class is associated to a score to the purpose of performing an easy combination of all the values and coming to the definition of a vulnerability index, expressed as a numeric value within a pre-defined range. This procedure allows for the possibility of specifying weighting coefficients for the different categories of parameters, thus accounting for the different relevance of the vulnerability categories onto the global vulnerability evaluation.

Scores and weighting coefficients will be defined for the illustrated procedure also. In the beginning, the choice will be in line with the existing vulnerability procedures, considering that such values should be based on the results of a wide statistical investigation.

However, it is believed that, mainly in the case of an aggregate resulting from the assemblage of several structural units, a single numerical value might not be representative of the real vulnerability conditions, or even misleading in the case of local critical conditions within a generally sound context. For this reason it has been planned to provide, as the main result of this vulnerability analysis, plant views of the aggregate showing, through colored maps, the distribution of the most critical vulnerability parameters. In this way, local critical situations will be easily recognizable.

## **CONCLUSIONS**

A renovated interest is present in the research community for seismic vulnerability analyses of buildings, in line with the original meaning of fast qualitative evaluations of the susceptibility to suffer damage from earthquakes. This is due, on the one side, to the need of Civil Protection Services to develop damage scenarios and emergency plans; on the other side, the qualitative approach to the analysis of the seismic performance of masonry buildings has widely improved in recent times.

The continuous progress in earthquake engineering studies, with special reference to the case of existing buildings, is also reflected in the new approach to vulnerability analyses

through the introduction of different knowledge levels, taking advantage of preliminary information coming from the analysis of archival documentation.

The development of a new procedure for vulnerability analyses, as it has been presented in this work with reference to the special case of structural aggregates in historical centers, has to face still now the problem of defining meaningful numerical values for the different evaluation parameters. The solution to this problem necessarily requires the recourse to a wide statistical campaign. In general, the formulation of a meaningful procedure for seismic vulnerability analyses still remains a complex problem, also in consideration of the need to develop an fast, clear, and stable procedure, suitable for the use by a wide community of technicians.




**Figure 3:** Fragilities in the structural units: a) porch and b) covered walkways.



**Figure 4:** Fragilities in the structural units: a) slender elements; b) elements protruding on the road.

## REFERENCES

- [1] Benedetti, D., Petrini, V., *Sulla vulnerabilità sismica di edifici in muratura: Proposta su un metodo di valutazione. L'industria delle Costr.* (1984) **149**, 66–74.
- [2] Giuffrè, A. *Sicurezza e conservazione dei centri storici: il caso Ortigia*. Laterza, (1993).
- [3] Aguado, J.L.P., Ferreira, T.M., Lourenço, P.B., The Use of a Large-Scale Seismic Vulnerability Assessment Approach for Masonry Façade Walls as an Effective Tool for Evaluating, Managing and Mitigating Seismic Risk in Historical Centers. *Int. J. Archit. Herit.* (2018) **12**, 1259–1275.
- [4] Petrini, V., Sede indagine: regione Lombardia, provincia Brescia (1995).
- [5] Carocci C. et al, *Il caso di Faenza (RA)- Identificazione preliminare delle caratteristiche degli aggregati del centro storico e delle vulnerabilità osservate*, (2011).
- [6] Carocci C. et al, *Piano di Ricostruzione del centro storico di Fossa (AQ)* (2012).
- [7] Rondelet, J. *Traité théorique et pratique de l'art de bâtir*. Parigi, Francia, 1802-1817, in : Tocci, C., Masiani, R., Lagomarsino, S., Cocina, S., Carocci, C. F., *Sicurezza e conservazione degli edifici storici monumentali*, pag. 78, ed. Gangemi Editore (2016).
- [8] Vicente, R., Parodi, S., Lagomarsino, S., Varum, H., Mendes Silva, J. A. R., Seismic vulnerability and risk assessment: case study of the historic city centre of Coimbra, Portugal, *Bull Earthquake Eng - © Springer Science+Business Media* (2011).
- [9] Ferreira, T.M., Maio, R., Vicente, R., Analysis of the impact of large scale seismic retrofitting strategies through the application of a vulnerability-based approach on traditional masonry buildings. *Earthq. Eng. Eng. Vib.* (2017) **16**, 329–348.
- [10] Ferreira T.M., Mendes N., Silva R., Multiscale Seismic Vulnerability Assessment and Retrofit of Existing Masonry Buildings, *MDPI Journal* (2019).
- [11] Formisano, A., Florio, G., R. Landolfo, Mazzolani, F. M., *Un metodo per la valutazione su larga scala della vulnerabilità sismica degli aggregati storici*, ANIDIS. Bari, (2011).
- [12] Bernardini, A., Giovinazzi S., Lagomarsino S., Parodi S. *Vulnerabilità e previsione di danno a scala territoriale secondo una metodologia macrosismica coerente con la scala EMS-98*. Convegno A.N.I.D.I.S. Pisa, Italia, (2007).
- [13] Dolce, M., Masi, A., Marino, M., Vona, M., Earthquake damage scenarios of the building stock of Potenza (Southern Italy) including site effects. *Bull. Earthq. Eng.* (2003) **1**, 115–140.
- [14] Braga, F., Dolce, M., Liberatore, D. *A statistical study on damaged buildings and an ensuing review of the MSK-76 scale*. In Proceedings of the 7th European Conference on Earthquake Engineering, Athens, Greece, 20–25 September (1982) pp. 431–450.
- [15] ATC-13. Earthquake Damage Estimation Data for California; Report ATC-13; Applied Technology Council: Redwood City, CA, USA, (1985).
- [16] Faccioli, E., Pessina, V., Calvi G. M. and Borzi, B., A study on damage scenarios for residential buildings in Catania city, *Article in Journal of Seismology* (1999) **3**, 327–343.
- [17] L. Berto, P. Faccio, A. Saetta, D. Talledo, I. Zamboni, 2017, *Valutazione di vulnerabilità sismica di edifici complessi/in aggregato: metodi di primo livello*, in : Atti del XVII Convegno Nazionale ANIDIS, L'ingegneria sismica in Italia (Pistoia, 17-21 settembre 2017), Pisa University press, Pisa.
- [18] PCM-DPC. Manuale compilazione scheda di 1° livello di rilevamento danno, pronto intervento e agibilità per edifici ordinari nell'emergenza post-sismica (AeDES) (2014).



**CIMNE**<sup>9</sup>

International Center  
for Numerical Methods in Engineering