
**XIV Convegno della rete Italiana LCA
IX Convegno dell'Associazione Rete Italiana LCA**

**La sostenibilità della LCA tra sfide globali e
competitività delle organizzazioni**

**Cortina d'Ampezzo
9-11 dicembre 2020**

A cura di Erika Mancuso, Sara Corrado, Arianna Dominici Loprieno, Laura Cutaia

1222 • 2022
800
ANNI



UNIVERSITÀ
DEGLI STUDI
DI PADOVA

ENEA

AGENZIA NAZIONALE PER LE NUOVE TECNOLOGIE,
L'ENERGIA E LO SVILUPPO ECONOMICO SOSTENIBILE

Rete Italiana LCA



La sostenibilità della LCA tra sfide globali e competitività delle organizzazioni

ATTI
del XIV Convegno della rete Italiana LCA -
IX Convegno dell'Associazione Rete Italiana LCA

Cortina d'Ampezzo
9-11 dicembre 2020

A cura di Erika Mancuso, Sara Corrado, Arianna Dominici Loprieno, Laura Cutaia

La sostenibilità della LCA tra sfide globali e competitività delle organizzazioni

Atti del del XIV Convegno della rete Italiana LCA - IX Convegno dell'Associazione Rete Italiana LCA
Cortina d'Ampezzo 9-11 dicembre 2020

A cura di Erika Mancuso, Sara Corrado, Arianna Dominici Loprieno, Laura Cutaia

ISBN: 978-88-8286-416-3

2021 ENEA

Agenzia nazionale per le nuove tecnologie, l'energia e lo sviluppo economico sostenibile

Copertina: Flavio Miglietta

Stampa: Laboratorio Tecnografico ENEA - Centro Ricerche Frascati

Comitato Scientifico	5
Comitato Organizzatore.....	7
Programma	8
SESSIONE I - Sostenibilità Agroalimentare	17
Impronta ambientale delle soluzioni di confezionamento del Grana Padano DOP	18
Analisi dell’impatto ambientale della produzione di carne bovina in un sistema di allevamento semi-intensivo in Paraguay.....	27
Sviluppo di un database italiano di Life Cycle Inventory dei prodotti agroalimentari: la metodologia	37
Assessment of carbon footprint of Italian red wines	46
Lo stoccaggio di carbonio organico nei suoli come indicatore addizionale negli studi di Product Environmental Footprint: il modello RothC applicato a un uliveto biologico in Italia	56
La definizione dei sistemi di prodotto di riferimento negli standard ISO 14000: applicazione nel Passaporto Ambientale per i prodotti agroalimentari della Montagna Vicentina	65
Impatto ambientale della coltivazione in pieno campo della canapa industriale (Cannabis sativa L.): valutazione di differenti itinerari tecnici.....	75
Profili ambientali di prodotti Made in Italy.....	84
SESSIONE I – poster	96
LCA as a tool for measuring Sustainable Development Goals for food and biowaste. A review.....	97
Commodity Life Cycle Costing: un nuovo approccio per valutare l’uso delle risorse naturali nel corso del ciclo di vita	114
LCA approach for the C&D waste management system in different countries of the world.....	125
Measuring circularity in the tourism sector: a step forward.....	134
Emissioni provenienti dall’allevamento suinicolo: valutazione dell’impatto ambientale considerando l’utilizzo di uno scrubber per il trattamento dell’aria.....	146
LCA methodology application to assess the environmental impact of CCS and CCU: a review	155
An environmental life cycle assessment of paints and varnishes in the Italian production process.....	165
SESSIONE II - Sostenibilità nella Gestione dei Rifiuti.....	174
Influenza della tipologia di sacchetto nella valutazione LCA della filiera di gestione del rifiuto organico.....	175
Life Cycle Assessment della pirolisi di biomasse residuali dal settore agro – alimentare	185
Technical functionality as a basis for developing substitution coefficients in waste management Life Cycle Assessment studies	195
Environmental impacts evaluation of a ceramic industry processes through integration of Life Cycle Assessment and Risk Assessment	204

How can Life Cycle Assessment contribute to circular economy transition: hints from sustainability transition research.....	214
SESSIONE III - Sostenibilità in Edilizia	223
Life Cycle Assessment e monetizzazione degli impatti come strumenti di supporto alle politiche di circular economy nel settore edilizio.....	224
L'analisi LCA a supporto della sostenibilità delle imprese: prodotti edilizi in laterizio	234
Valutazione dei tempi di ritorno energetici e ambientali e della convenienza economica per la riqualificazione energetica di una scuola	245
Assessing maritime transport through LCA and LCC: a literature review	256
Life cycle assessment of AlTiN thin films deposited by magnetron sputtering	266
LCA di diverse configurazioni realizzative per un impianto fotovoltaico piano con moduli ad eterogiunzione.....	275
SESSIONE IV - Sostenibilità Circolare	285
Sviluppo della prima RCP nell'ambito dello schema "Made Green in Italy"	286
LCA-based material selection in the early stages of design: environmental benefits, tools, obstacles and opportunities	296
The new Guidelines for Social Life Cycle Assessment of products and related pilot phase: challenges and successes	306
Towards an LCA-based market incentive mechanism regulated through blockchain for carbon emissions reduction	313
Carbon footprint di uno stand espositivo	323
Valutazione preliminare in ottica di ciclo di vita della fattibilità di una filiera italiana del riciclaggio delle batterie elettriche per autotrazione	333
SESSIONE II - poster.....	342
Approcci LCA per la verifica di Tecnologie Reversibili per il riuso, la rigenerazione e il riciclo.....	343
Analisi di esperienze applicative LCA di edificio: differenze, complementarità, sinergie.....	353
A green chemistry case study: sensor-based methods for bioactive compounds determination in food	363
Circularità e sostenibilità nella digestione anaerobica.....	372
Comparative LCA of fossil fuels and biofuels use for transportation – A literature review	381
Life cycle inventories for modelling the production of battery electric vehicles in the European life cycle assessment studies	392
Do PCRs and EPDs need to be improved? Critical issues to EPD system with a focus on the construction sector	402
SESSIONE III – poster	411
Social Organizational Life Cycle Assessment (SO-LCA): un caso studio focalizzato sulla comunità locale.....	412
Analisi di letteratura e aspetti metodologici per LCA di batterie stazionarie.....	419
Long-term prospective LCA of emerging photovoltaics	429

Dalla PCR alla EPD: il percorso di sostenibilità dell'attività estrattiva del calcare micronizzato di Gola della Rossa Mineraria (Ancona)	437
L'utilizzo del Life Cycle Assessment nel settore della ristorazione. Una revisione sistematica della letteratura	446
Carbon footprint implications of using seawater and marine aggregates in concrete	459
Analisi del ciclo di vita del kWh Italiano	468
Evidences of human health damage mitigation associated with the Italian lockdown due to COVID-19 through the lens of energy metabolism assessment	479
Banca dati Italiana LCA: creazione di dataset sul mix elettrico nazionale	493
Performing a fast and effective Global Sensitivity Analysis using Python: a simplified example applied to the LCA of Italian electricity generation scenarios	503
Modeling combined heat and power plants in Life Cycle Assessment: a comparison among different approaches to deal with multifunctionality	515
PREMIO GIOVANI RICERCATORI.....	527
Temporal variability and Battery Electric Vehicles influence on LCA impacts of marginal electricity consumption in Italy	528
LCA- and LCC-based Solar Home Systems ecodesign	538

Carbon footprint implications of using seawater and marine aggregates in concrete

Valeria Arosio¹, Alessandro Arrigoni², Giovanni Dotelli¹

¹Dipartimento di Chimica, Materiali e Ingegneria Chimica, Politecnico di Milano, Piazza Leonardo da Vinci 32, Milano, 20133, Italy

²Denva - Demetra Società Cooperativa Sociale Onlus - Via Visconta 75, Besana Brianza (MB), 20842 Italia

Email: valeria.arosio@polimi.it

Abstract

The use of seawater and marine aggregates in concrete can significantly reduce the pressure on freshwater resources in areas characterized by low local water availability. However, possible burden shiftings have not been investigated yet. The present study investigates the carbon footprint implications of using seawater and marine aggregates in concrete mixes and analyses the trade-offs between water and carbon footprints. Geo-referenced data are used to explore the influence of the distance from the coast to the concrete batching plant. The use of seawater does not seem to increase the greenhouse gas emissions of concrete production in regions near the sea. However, using marine aggregates could significantly worsen the carbon footprint of concrete if the batching plant was distant from the coast.

1. Introduction

Among construction materials, concrete is the most used and the one that has experienced the faster growth in consumption in the last 50 years (Miller et al., 2016). Global water consumption related to its production has been estimated in 16.6 Gm³ in 2012, and it is expected to grow by more than 40% by 2050 if no action is taken (Miller et al., 2018). The production of 1 m³ of fresh concrete in Italy was estimated to require from 1.7 m³ to 5.5 m³ of freshwater, when all the life cycle stages of the production process (i.e., from the extraction of raw materials to the delivery to the construction site) are included. Although aggregate production proved to be the main responsible for freshwater consumption, it was estimated that the concrete mixing process itself contributes significantly to the total consumption (Arosio et al., 2019). A solution that has been explored to reduce the pressure on freshwater resources is the substitution of freshwater with seawater in the concrete mixing process. Even though the use of seawater is currently forbidden in many countries to prevent the corrosion of the steel rebars (Redaelli et al., 2019), the use of alternative non-corrosive reinforcing materials (e.g., glass fiber-reinforced polymer, stainless steel) could pave the way to the use of salt-contaminated water and aggregates (Younis et al., 2020). A recent study showed that when seawater is used in combination with reinforcing elements resistant to corrosion, the mechanical properties and durability of concrete can be preserved or even improved (Nanni, 2015).

In a previous research, the water scarcity footprint (WF) implications of substituting freshwater with seawater and land-won aggregates with unwashed marine aggregates have been investigated for the Italian context. The AWARE method (Boulay et al., 2018) was used for the assessment, and the use of seawater in the mixing process proved to effectively reduce the WF of concrete in areas affected by water scarcity (e.g., up to 17 m³ world equivalent of water per m³ of concrete in eastern Sicily). Moreover, if land-won aggregates were also substituted with their marine counterpart, a WF reduction of more than 80% could be achieved in arid regions. However, although the study clearly showed the benefits in terms of freshwater availability of using marine resources, possible unintended consequences in other areas of interest (i.e., burden shiftings) have not been investigated. The present study aims therefore to uncover one of these potential burden shiftings due to a change in the mix design: the climate implications. The goal is to compare the life cycle greenhouse gas emissions of the innovative concrete mix designs to the ones emitted by traditional mixes. To do so, the greenhouse gas emissions linked to the extraction of marine aggregates and seawater, and their transport from the coast to the batching plants are explored. This study is intended to provide new insights to policymakers and concrete industry in order to avoid the adoption of a technology that presents more drawbacks than advantages.

2. Goal

The goal of this study is to assess the variation in the carbon footprint (CFP) of concrete production in Italy if seawater and marine aggregates were used instead of seawater and land-won aggregates.

3. Scope

The CFP of three concrete mixes are compared: 1) the reference mix, made with land-won aggregates and freshwater (LAFW); 2) a concrete mix made with land-won aggregates, but using seawater instead of freshwater for mixing (LASW); and 3) a concrete mix made with marine dredged aggregates instead of land-won ones, and seawater for mixing (MASW). The reference mix (LAFW) is modelled based on the Italian current practice, while the other scenarios (i.e., LASW and MASW) are hypothetical scenarios aimed to investigate the implications of using seawater and marine aggregates in Italy. It's worth noting that new infrastructure would be required in Italy if the new mix designs were adopted. The development and costs of this new infrastructure are outside the scope of this study.

The functional unit adopted for the assessment is 1 m³ (2370 kg) of unreinforced generic fresh concrete supplied to the building site. All mixes are assumed to require the same proportion of aggregates, water, and cement (i.e., 1280 kg of gravel, 720 kg of sand, 170 litres of water, and 200 kg of Portland cement per m³ of concrete). The recipe for the mix is taken from the ecoinvent database (Wernet et al., 2016), and it represents the composition of a general unreinforced concrete. The mechanical properties and the service life of concrete are assumed to be unaffected by the type of aggregates and water used, and therefore they are considered the same for the three mix designs.

Three Italian regions differing in water availability and distance from the sea are used as case studies: Abruzzo, eastern Sicily and Lombardy.

4. Product system scenarios

The system boundaries of the assessment include all processes from raw material extraction through to the delivery of fresh concrete to the construction site, as illustrated in Figure 1.




Figure 1: flow chart of the product system analysed. The gate of the analysis is the delivery of concrete to the construction site. Depending on the scenario, water for mixing the concrete is collected from a well located at the batching plant or from the sea, water transport by tanker is needed only in the latter case

In LAFW and LASW, land-won aggregates are considered as supplied from the most common types of quarries available in Italy: dry quarries, wet quarries, and rock quarries. Quarrying operations in dry quarries occur above the water table. Conversely, sand and gravel are dredged from below the water level in wet quarries, causing the formation of a lake. Aggregates from rock quarries are obtained by blasting and crushing stones from hard rock formations. In MASW, marine aggregates are assumed to be dredged from the seabed close to the Italian coastline, and then transported by ship to the shore to be processed. This is a hypothetical scenario since mining of marine aggregates is not currently practiced in Italy. Data for modelling marine aggregates dredging, transport and processing rely on information available in the UK and the Netherlands, where marine dredging is a common practice (Kemp, 2008). In LASW, freshwater for mixing concrete in the reference mix is considered as collected from a well located at the batching plant; hence, there is no transportation of mixing water. In the other scenarios, water for mixing is assumed to be withdrawn from the sea by an open intake facility situated 500 meters from the coast (Shahabi et al., 2015) and then transported by tanker to the batching plants.

5. Life Cycle Inventory

Both primary and secondary data are used for the assessment. Primary data are collected in a wet quarry and in a batching plant. When primary data are not available, secondary data from scientific literature, reports and ecoinvent 3.3 database (Wernet et al., 2016) are used. The Italian electricity mix is applied to model the electricity consumed in quarries, cement factories and batching plants. The energy consumption and the source of data for aggregates production, water collection and batching plant operations are listed in Table 1. Cement production is modelled based on the information reported for portland cement in ecoinvent 3.3.

Regarding plant locations and distances, geodata related to active quarries are collected from the official websites of the analysed regions. Location of cement factories and batching plants are sourced, respectively, from the Italian Association of Cement manufacturers (AITEC, 2019) and the Italian Technical Economic Association for Ready-Mixed Concrete (ATECAP, 2019). It is assumed that each batching plant acquires aggregates in equal amount from the closest four quarries, and cement from the closer cement factory. The closer facilities are identified via ArcGIS. For simplicity, seawater intake facilities and wharves for marine aggregates discharging are assumed to be located along the coastline, at the minimal straight-line distance from the batching plant that is supplied. Road distances between the batching plants and the selected suppliers were calculated by Distance Matrix API of Google. An average distance of 10 km is assumed for the transport of concrete to the construction site (ANCE, 2012).

Table 1: energy consumption for production of aggregates, water collection and activities occurring in the batching plant, referred to the functional unit (i.e. 1 m³ of fresh concrete produced with 1280 kg of gravel, 720 kg of sand, 170 litres of water, and 200 kg of cement)

Process unit	Consumption	UM ^a	Qty	Source (Reference)
Aggregates production (Rock quarry)	Electricity	kW h	6.66	Primary data
	Diesel	MJ	13.16 ^b	Primary data
Aggregates production (Dry quarry)	Electricity	kW h	2.70	(Rigamonti, et al. 2017)
	Diesel	MJ	24.20 ^b	(Rigamonti, et al. 2017)
Aggregates production (Wet quarry)	Electricity	kW h	4.00	(Regione Piemonte, 2014)
	Diesel	MJ	43.60 ^b	(Regione Piemonte, 2014)
Aggregates production	Electricity	kW h	3.00	(Kemp,2008)

Process unit	Consumption	UM ^a	Qty	Source (Reference)
(Off-shore)	Diesel	MJ	43.60	(Kemp,2008)
Water collection (well)	Electricity	kW h	0.0678	Ecoinvent 3.3
Water collection (sea)	Electricity	kW h	0.0085	(Shababi, et al., 2015)
Concrete production in batching plant	Electricity	kW h	3.85	Primary data
	Diesel	MJ	0.20	Primary data
	Thermal Energy	MJ	5.00	Ecoinvent 3.3
^a All quantities are referred to 1 m ³ of fresh concrete				
^b Calculated considering density of fuel oil equal to 0.82 kg/l and calorific value equal to 42.7 MJ/kg.				

6. Life Cycle Impact Assessment

The CFP assessment is standardized by ISO 14067 (ISO, 2018): “Greenhouse gases - Carbon footprint of products - Requirements and guidelines for quantification”. CFP aims to quantify the greenhouse gas emissions of a product or activity through their life cycles. The IPCC 2013 method available in Simapro 8.5 (i.e., GWP100) is used for assessing the CFP. The method uses IPCC characterization factors to quantify the relative global warming impacts of various gases in terms of kg CO₂-equivalents per kg of greenhouse gas, and it does not account for indirect effects (Intergovernmental Panel on Climate Change, 2013).

7. Results and discussion

The resulting CFP for each of the three concrete mixes in each of the regions analysed are presented in Figure 2. An average of 145 kg of CO₂ eq. are estimated to be emitted to produce 1 m³ of the reference mix in Abruzzo and Lombardy, while the CFP of concrete in eastern Sicily results to be slightly higher (i.e., 158 kg of CO₂ eq. per m³) due to the longer distances covered to transport the land-won aggregates. Nevertheless, most of the emissions (i.e., around 80%) are caused by cement production.

To allow a more complete comparison between different scenarios, the WF of each scenario for each region are reported in Figure 3. The WF results were calculated in previous study (Arosio et al., 2019) and are here updated, consistently with the hypothesis on raw materials suppliers described in the inventory phase.

Although replacing freshwater with seawater would cause an average reduction of the WF of 7% in Abruzzo and eastern Sicily, it would slightly increase in the

CFP (by 2% and less than 0.6% in the two regions, respectively). In Lombardy, the increase of CFP is higher (from 2% to 5%) due to the greater distances covered by the tankers to transport seawater, while the WF savings were lower than the other regions (less than 2%). Therefore, the freshwater replacement is certainly convenient in terms of WF, while the result of CFP is not conclusive in view of low percentage improvements/worsenings.

Introducing marine aggregates results in significant increase of the CFP in almost all the cases considered. The CFP for marine aggregates production, in fact, results to be higher than the CFP related to land-won ones for all the type of quarries. The CFP of marine aggregates is estimated to be 10.8 kg CO₂ eq. per ton of aggregates produced; while the CFP of land-won aggregates is estimated to be 1.8 kg CO₂ eq. per ton produced in dry quarries, 3.0 kg CO₂ eq. per ton in rock quarries, and 2.2 kg CO₂ eq. per ton in wet quarries. The impact of transporting the aggregates to the batching plant results particularly significant in Lombardy and Abruzzo, due to the long distance from the coast. Four batching plants in Sicily showed an opposite trend: being situated near the coast, the emissions to extract, process, and transport marine aggregates result to be lower than transporting aggregates from farther land quarries. At the same time, the impacts on freshwater resources in Abruzzo and Eastern Sicily would significantly reduce (from 45% to 80%). In Lombardy, the WF decreases (up to 36%) only if marine aggregates are used in place of land-won aggregates from wet quarries; otherwise, WF would increase compared to the reference mix due to the long distance from the coast.




Figure 2: CFP of 1 m³ of fresh concrete delivered to the construction site in the three scenarios for each of the three regions. The histogram bars indicate the calculated regional average, while the error bars show the minimum and the maximum CFP in the region. Aggregate production phase includes extraction (of land-won aggregates) or dredging and shipping (of marine aggregates), and processing of aggregates




Figure 3: WF of 1 m³ of fresh concrete delivered to the construction site in the three scenarios for each of the three regions. The histogram bars indicate the calculated regional average, while the error bars show the minimum and the maximum WF in the region. The diagonal lines highlight direct WF, the solid fill represents indirect WF

8. Conclusions

The greenhouse gas consequences of using seawater to mix concrete instead of freshwater and of substituting land-won aggregates with marine ones have been assessed for three Italian regions. The results have been compared to the water footprint implications assessed in a previous study.

The carbon footprint implications of using seawater are strongly correlated to the geographical position. In the case of batching plants located near the coast, the use of seawater would have an almost negligible effect on the carbon footprint of concrete (e.g., always lower than a 0.6% increase for plants located in eastern Sicily). At the same time, using seawater in the concrete mix would significantly reduce its water footprint in water stressed regions such as eastern Sicily. Conversely, when the batching plants are situated inland, the carbon footprint implications of using seawater increase significantly (i.e., up to a 5% increase in the CFP of concrete produced in Lombardy). At the same time, Lombardy (i.e., the inland region investigated in the paper) has a larger freshwater availability and, therefore, the water footprint benefits of using seawater in the concrete mix are strongly reduced.

The use of unwashed marine aggregates (and seawater for mixing) could significantly reduce the water footprint of concrete in Abruzzo and some batching plants of Lombardy (i.e., up to 35%), and in eastern Sicily (i.e., up to 80%). Where batching plants are close to the coast (i.e., eastern Sicily), introducing marine aggregates results in a small positive or negative variation of carbon footprint. Conversely, in Abruzzo and Lombardy the carbon footprint would strongly

increase due to the distance from the coast; hence in these regions the choice of the type of aggregates imply a trade-off. Finally, where aggregates need to be transported over long distances and the watershed has a large availability of freshwater, using marine aggregates might be disadvantageous for both the water footprint and the carbon footprint.

9. Further investigations

This analysis is intended to pave the way to further investigations about the environmental implications of using seawater and marine aggregates together with non-corrosive reinforcements in concrete structures. In order to extend the analysis to the complete life cycle of the structure, the durability of the new mix designs and the burdens associated to the manufacturing of the reinforcing elements should be explored. Additional sensitivity analysis considering different concrete types, transportation modes for water and fresh concrete need to be investigated further too. Finally, a life cycle cost analysis would provide useful information regarding the economic feasibility of using seawater and marine aggregates in concrete.

10. References

AITEC, 2019. Pubblicazioni tecnico economiche, viewed 18 Mar 2019, <https://www.aitecweb.com/Pubblicazioni/Pubblicazioni-Tecnico-Economiche>

ANCE, 2012. Una proposta concreta dell'ance per un efficace contrasto alle infiltrazioni della criminalità organizzata nel settore delle costruzioni, ANCE (Associazione Nazionale Costruttori Edili), Roma, Italy.

Arosio, V, Arrigoni, A, Dotelli, G, 2019. Reducing water footprint of building sector: Concrete with seawater and marine aggregates, in: IOP Conf. Ser.: Earth Environ. Sci. 323, 012127, Sustainable Built Environment D-A-CH Conference 2019, Graz, Austria, 11–14 Sep.

ATECAP, 2019. Impianti soci ATECAP, viewed 18 Mar 2019, <http://www.atecap.it/t>

Boulay, AM, Bare, J, Benini, L, Berger, M, et al., 2018. The wulca consensus characterization model for water scarcity footprints: Assessing impacts of water consumption based on available water remaining (aware). Int. J. Life Cycle Assess. 23, 368-78.

Intergovernmental Panel on Climate Change, 2013. Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change. Cambridge, UK and New York, NY, US.

ISO, 2018. ISO 14067:2018 Greenhouse gases — Carbon footprint of products — Requirements and guidelines for quantification.

Kemp, R, 2008. Energy Consumption of Marine Aggregate Extraction. The Crown Estate.

- Miller, SA, Horvath, A, Monteiro, PJM, 2018. Impacts of booming concrete production on water resources worldwide. *Nat. Sustain.* 1, 69–76.
- Miller, SA, Horvath, A, Monteiro, PJM, 2016. Readily implementable techniques can cut annual CO₂ emissions from the production of concrete by over 20%. *Environ. Res. Lett.*, 11, 074029.
- Nanni, A, 2015. Seacon sustainable concrete using seawater, salt-contaminated aggregates, and non-corrosive reinforcement, viewed 18 Mar 2019 <http://seacon.um-sml.com/>
- Redaelli, E, Arrigoni, A, Carsana, M, Dotelli, G, et al., 2019. Culvert Prototype Made with Seawater Concrete: Materials Characterization, Monitoring, and Environmental Impact. *Adv. Civ. Eng. Mater.*
- Regione Piemonte, 2014. Documento di programmazione delle attività Estrattive (DPAE) - Primo Stralcio - Volume 2.
- Rigamonti, L, Pantini, S, Borghi, G, 2017. Relazione finale valutazione con metodologia LCA (life cycle assessment) dei flussi e del destino dei rifiuti da costruzione e demolizione, Centro Studi MatER Piacenza, Italy, p. 293.
- Shahabi, MP, McHugh, A, Ho, G, 2015. Environmental and economic assessment of beach well intake versus open intake for seawater reverse osmosis desalination. *Desalination.* 357, 259-266.
- Wernet, G, Bauer, C, Steubing, B, Reinhard, J, Moreno-Ruiz, E, Weidema, B, 2016. The ecoinvent database version 3 (part i): Overview and methodology *Int. J. Life Cycle Assess.* 21, 1218-30.
- Younis, A, Ebead, U, 2020. Long-Term Cost Performance of Corrosion-Resistant Reinforcements in Structural Concrete, in: *The International Conference on Civil Infrastructure and Construction (CIC 2020)*, Doha, Qatar, Feb. 2020.

Con il patrocinio di:



COMUNE DI CORTINA D'AMPEZZO



MINISTERO DELL'AMBIENTE
E DELLA TUTELA DEL TERRITORIO E DEL MARE



ENEA

ISBN 978-88-8286-416-3